



## ULTRA CLEAR™ TOUCH PANEL SYSTEMS

### ONE SYSTEM - TWO CHOICES HOW TO USE THE ULTRAPURE WATER:

The Ultra Clear™ TP systems have a fixed water dispenser and an optional flexible dispenser to bring the water to your work.

The systems provide you the best solution for all water quality demands and applications in your laboratory.

#### New look - new performance

- 7" multi-color glass display for fast and easy operation, with a generous overview
- Easy to navigate by touching functional system components
- New designed user interface
- Graphic display of all main functions
- SD cards and USB connection for data transfer

Each system is equipped with economical state-of-the-art purification technology.

Water quality with a resistivity of 18.2 MΩcm and a TOC level between 1 - 3 ppb far exceeds all reagent water quality standards including: ASTM Type 1, CLSI and ISO 3696 Type 1. All systems that include ultrafiltration (UF) produce the highest possible water quality. These units deliver RNase-, DNase- and DNA-free water.

Systems with UF are also capable of producing purified water with endotoxin levels of < 0.001 EU/ml.

The flow rate of ultrapure water is up to 2 l/min. The high resolution display indicates the water conductivity in μS/cm or resistivity in MΩ-cm with the corresponding water temperature.


Consumable change is very simple and fast due to quick and easy access to the replacement parts. A single UV bulb is used for the oxidation of organic compounds and TOC measurement.

### TYPICAL APPLICATIONS

#### Ultra Clear™ TP UV TM and UV UF TM:

- HPLC
- IC
- GC and GC/MS
- TOC analysis
- ICP and ICP/MS
- DNA sequencing
- RNase- and DNase-free
- DNA-free
- PCR
- IVF
- 2-D-electrophoresis
- critical cell and tissue culture
- pyrogen sensitive applications





FLWSHEET OF ULTRA CLEAR TP UV UF TM SYSTEM

The use of a single UV lamp results in much lower annual running cost compared to the competition.

The energy saving operation mode enables the user to program the running cycles according to the real needs.

A built-in automatic self-cleaning/sanitization mode extends the life of the ultrafiltration module.

All Ultra Clear™ TP systems are delivered with the first set of all cartridges and filters.

## ULTRA CLEAR™ TP SERIES SYSTEM

		UV TM	UV UF TM
<b>Ultrapure water specifications</b>			
Output up to	l/min	2	2
Conductivity at 25° C	µS/cm	0.055	0.055
Resistivity at 25° C	MΩ-cm	18.2	18.2
TOC	ppb	< 1 - 3	< 1 - 3
DNase, RNase, DNA		-	free
Bacteria	cfu/ml	< 1	< 1
Endotoxins	EU/ml	-	< 0.001
Particles > 0.2 µm	per ml	< 0.1	< 0.1
<b>Feed water specification</b>			
Pressure	bar	0.1 - 5	0.1 - 5
Conductivity	µS/cm	< 20	< 20
CO <sub>2</sub> max.	mg/l	15	15
TOC	ppb	< 50	< 50
Temperature	°C	5 - 35	5 - 35
Shipping weight	kg	26	26
Power supply	V/Hz	100 - 240 / 50 or 60	
Dimension H/W/D	mm	530/340/320	
<b>Catalog Number</b>		<b>W3T360165</b>	<b>W3T360166</b>



STERILE FILTER



OPTIONAL FLEXIBLE SIDE DISPENSER

## CONSUMABLES

Item	Change frequency	Cat.No.
Deionization module VMD for applications in the inorganic range	6 – 12 monthly	<b>W3T197618</b>
Pretreatment module DTO for applications that need low TOC	6 – 12 monthly	<b>W3T197621</b>
Polishing module MF III D for applications in the low TOC range	6 – 12 monthly	<b>W3T197694</b>
Polishing module ILT for inorganic applications	6 – 12 monthly	<b>W3T199853</b>
Sterile filter 0.2 µm, 1000 cm <sup>2</sup>	6 monthly	<b>W2T526542</b>
Disinfection kit (pack of 3)	-	<b>W3T199768</b>
UV replacement bulb for systems with and without TM	12 monthly	<b>W2T558521</b>
Ultrafiltration module	18 – 36 monthly	<b>W3T197614</b>

Consumable change frequency information is average and can vary.

## OPTIONS

Item	Cat.No.
Remote dispense station	<b>W3T368947</b>

## ACCESSORIES

Item	Cat.No.
Flexible side dispenser (Ultra Clear)	<b>W3T360439</b>
Degassing unit 10 – 150 l/h to reduce CO <sub>2</sub> in the inlet water which is increasing the cartridge life time	<b>W3T314413</b>
Data analysis tool Ultra Clear TP History	<b>W3T370122</b>



OPTIONAL FLEXIBLE SIDE DISPENSER, DETAIL



DTO MODULE



PL 16 (Palokorvenkatu 2)  
04261 Kerava  
Puh. 010 417 4500  
hyxo@hyxo.fi • www.hyxo.fi

Fahrenberg 8, 22885 Barsbüttel, Germany

+49 (40) 670 868-6 sales.lab.de@evoqua.com [www.evoqua.com/en/brands/lab](http://www.evoqua.com/en/brands/lab)

Ultra Clear is a trademark of Evoqua, its subsidiaries or affiliates, in some countries.

All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2016 Evoqua Water Technologies GmbH

Subject to change without notice

LAB-UCTP-DS-EN-0916